

IN YOUR KIT

Quick Connect coupling | Male plug | Spare EPDM seal | Water-hose gasket

A spare seal and hose gasket are included for your convenience.

SIX STEPS TO A VERIFIED INSTALLATION**1 CHOOSE A SECURE DECK PROFILE**

Rotate rear legs for a stable frame on your coping; select the fit shown below.

**Flat | legs back****Flat | legs forward****Tapered coping****Raised edge****2 POSITION THE FRAME**

Place the white frame on the pool coping. Keep the upright pipe straight and the black float assembly freely hanging in the pool.

3 ADJUST THE WATER LEVEL

Gently twist or rock the black assembly up or down on the pipe (about 4-9 inches). Set its bottom edge near skimmer center; raise for a higher level.

4 ATTACH AND LOCK THE QUICK CONNECT

Turn the faucet OFF. Seat the EPDM seal, tighten the fitting hand-snug, and follow these pictures:

STEP 1
ALIGN BOTH PIECES
IN BOTH HANDS.**Align halves****STEP 2**
PULL BACK SLIDE
& INSERT MALE PLUG**Slide collar; insert plug****STEP 3**
RELEASE SLIDE ONCE
MALE PLUG IS
INSERTED**Release collar; verify lock**

No tools or thread tape. Use the collar to disconnect; never remove the factory-installed nozzle.

5 REDUCE FLOW & TEST MANUAL SHUTOFFOpen faucet to **no more than a steady stream**. Less flow is sufficient for maintaining pool level, may reduce water loss if a hose fails, and is quieter. Lift the internal float: **all flow stops**. Lower it: flow resumes.**6 VERIFY AUTOMATIC SHUTOFF**Remain present while the water reaches the selected level at the **bottom edge of the black assembly**. Confirm flow stops. If water continues rising, shut off faucet and investigate.**CONNECTION CARE & TROUBLESHOOTING****EPDM SEAL: ORIENTATION & FIT**The seal's **recessed side must be visible from the threaded end**. Seat correctly; hand-tighten only until snug. Overtightening can crush the seal and cause leaks. **No tools**.**DO NOT REMOVE THE NXGEN NOZZLE****Do not remove the NXGEN nozzle from the tank assembly.** Removing the factory-installed nozzle will cause continuous filling and can overflow the pool. Disconnect with the collar.**If no flow:** check faucet, hose and inlet. **If coupling leaks:** check EPDM orientation and snug connection.**SAFETY, HOSE MATERIALS & SEASONAL CARE**

Keep the hose flat and away from foot traffic; remove the unit from the deck during gatherings. Avoid aluminum hose ends: dissimilar-metal contact with brass/stainless fittings can cause galvanic corrosion. Inspect connections periodically. Before freezing weather, disconnect, drain and remove the unit.

BEFORE LEAVING THE WATER SUPPLY UNATTENDED

- | | | |
|---|---|--|
| ☐ Frame supported | ☐ Quick Connect dry / locked | ☐ Hose / walking path clear |
| ☐ EPDM seal seated | ☐ Manual shutoff tested | ☐ Automatic shutoff tested |

LIMITED ONE-YEAR WARRANTY

The original retail purchaser has a Limited One-Year Warranty for qualifying defects under normal residential use, subject to the complete published warranty terms and exclusions.

Warranty: staypoolizer.com/pages/warranty | Support: contact@jcscoinc.com